



Complete range in Basic dishes - carefully designed to give the best value in price and quality

The mechanical parts of the Basic dishes have been created with careful attention to detail and recommendations from installers. The dishes are manufactured using a fine anti-corrosive treatment

- Improved, maintenance-free reception
- Polyester powder-coated
- Computer aided design for high performance
- Easy to install
- 50 cm, 60 cm, 75 cm and 85 cm size options
- Pole mount
- Easy adjust elevation scale
- 100 pcs bulk pack



Ral 7035

Technical data on Basic dishes

Type		Basic 60	Basic 60 w. south bracket	Basic 75	Basic 85
Size		60 x 65 cm	60 x 65 cm	70 x 78 cm	85 x 95 cm
Part No. (light grey)	Ral 7035	128601	128602	128701	128801
Frequency range	GHz	10.7 - 12.75	10.7 - 12.75	10.7 - 12.75	10.7 - 12.75
Gain @ 11.7 GHz	dBi	35.8	35.8	37.1	38.8
G/T LNB 0.7 dB	dB/K	16.0	16.0	17.3	19.2
X-polarisation	dB	> 27	> 27	> 27	> 27
Offset angle	degrees	26	26	26	26
Elevation range	degrees	10 - 50 45 - 80	10 - 50 45 - 80	10 - 60	10 - 60
Reflector type	F/D 0.6	Offset	Offset	Offset	Offset
Beam width	degrees	3.1	3.1	2.6	2.0
Windload @ 42 m/s	N	445	445	619	902
Material		Galv. steel	Galv. steel	Galv. steel	Galv. steel
Finish		Polyester powder coat	Polyester powder coat	Polyester powder coat	Polyester powder coat
Aluminium LNB holder	mm	Ø40 + Ø25	Ø40 + Ø25	Ø40	Ø40
Mast dimension	mm	Ø28 - 60	Ø28 - 60	Ø32 - 60	Ø32 - 60
Wall bracket		- optional extra	- optional extra	- optional extra	- optional extra
Remarks					



Basic duo-block



Basic flexi-block

We can supply a wide range of different LNB brackets for the Basic-series dishes

- more detailed information on page 91 under LNB-brackets



Basic multi-block